Product sheet



Surface Panel Square 25W CCT iSG Lighting

Brand: LEDME

Reference: LEDME GA5638

Square surface panel from the Pro Series by iSG Lighting with CCT technology and 25W power. Incorporates Ledvance source, reaches 2500 lumens and 100 lm/W efficiency. Operates between -20°C and 45°C with a 120° angle and 30000 hour lifespan. Built in aluminum with Lifud driver, CRI 80, UGR <19 and IP20 protection for safe installations.

View product online

Description

The iSG Lighting Pro Series Square Surface Panel 25W CCT is an LED lighting device designed for surface mounting, offering an efficient and versatile solution. With Ledvance technology and Lifud driver, it ensures optimal performance in various environments.

Technical Specifications

- Watts: 25 w
- Luminous Flux: 2500 lm
- Efficiency: 100 lm/W
- Operating Temperature: -20°C ~ + 45°C
- Emission Angle: 120°
- Lifespan: 30000 hours
- Protection: IP20, IK5
- Insulation Class: II
- Supply Voltage: 170-265V ac
- Dimensions: 285x285x28H mm
- Material: Aluminum
- CRI: 80
- UGR: <19
- Power Factor: 0.5

- Dimmable: Optional
- Warranty: 5 years
- Color Temperature: 3CCT

Its low UGR index and high luminous efficiency make it suitable for spaces where glare control and energy saving are required, leveraging its aluminum construction for adequate thermal dissipation within its operating range.

Specifications

Appliance class	Class II
High	28H mm
Width	285 mm
Opening angle	120°
Cri (Ra)	80
Driver included	Yes
EAN	8435579756386
Manufacturer	iSG Lighting
Halogen-free	Yes
Lumens (lm)	2500 lm
Power (W)	25 W
Protection	IP20
Type of installation	Surface
Estimated life (h)	30000
Diameter (cm)	28,5 cm
Suitable for sloped ceiling	No

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 16 November 2026