Product sheet



Circular Surface Panel Pro Series 25W CCT

Brand: LEDME

Reference: LEDME GA5635

iSG Lighting Circular Surface Pro Series panel with CCT technology and Ledvance source. Offers 2500 lumens and 100 lm/W efficiency in an aluminum housing. Operates between -20°C and 45°C with a 120° beam angle and 30,000-hour lifespan.

View product online

Description

The iSG Lighting Circular Surface Pro Series 25W CCT LED panel is designed for recessed or surface mounting, offering an efficient and durable lighting solution with Ledvance source.

Technical Specifications

- Watts: 25 w
- Luminous Flux: 2500 lm
- Luminous Efficacy: 100
- Operating Temperature: -20°C ~ +45°C
- Beam Angle: 120°
- Lifespan: 30,000 hours
- Protection: IP20, Ik: 5
- Electrical Insulation Class: II
- Overvoltage Protection: 4 Kv
- Supply Voltage: 170-265v ac
- Dimensions: 285X28H mm
- Material: Aluminum
- Driver: Lifud
- CRI: 80
- UGR: <19
- Dimmable: Optional
- Color Temperature: 3CCT

With a low UGR index and high luminous efficacy, this panel ensures uniform and comfortable lighting. Its aluminum construction ensures the necessary heat dissipation to maintain performance throughout its long lifespan.

Surface mounting allows for easy integration into various indoor environments where precise light control is required, with dimming options available.

Specifications

Appliance class	Class II
Energy classification	A
EAN	8435579756355
Manufacturer	iSG Lighting
Suitable for sloped ceiling	No

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 10 November 2026