Product sheet



Circular Surface Panel Pro Series 12W CCT iSG Lighting

Brand: LEDME

Reference: LEDME GA5633

iSG Lighting Pro Series circular surface panel with Ledvance source and Lifud driver. It offers 1200 lumens, 100 lm/W efficiency and 120° angle. Operates between -20°C and +45°C with 30,000-hour service life, IP20 protection, Ik 5, Class II and 170-265V ac universal power supply.

View product online

Description

iSG Lighting's Pro Series Circular 12W CCT Surface Panel is a LED lighting device designed for surface installation, offering an efficient and versatile solution for various environments. Its aluminium construction ensures durability and adequate thermal dissipation within its operating range from -20°C to +45°C.

Technical characteristics

- Watts: 12 W
- Light Source: Ledvance
- Lightness: 1200 lm
- Efficiency: 100 lm/W
- Working temperature: -20°C ~ +45°C
- Emission angle: 120°
- Lifetime: 30,000 hours
- Protection: IP20, IK5
- Electrical insulation class: II
- Overvoltage protection: 4 kV
- Power supply: 170-265 V AC
- Dimensions: 170x28 mm
- Material: Aluminium
- Driver: Lifud

- CRI: 80
- Regulatory: Optional
- Guarantee: 5 years
- Color temperature: 3 CST

Given its high light performance and energy efficiency, this panel is suitable for spaces that require general lighting with low electrical consumption.

Specifications

Appliance class	Class II
High	28 mm
Bulb not included	No
Width	170 mm
Opening angle	120°
Cap	LED
Diameter	170 mm
Driver included	Yes
EAN	8435579756331
Manufacturer	iSG Lighting
Halogen-free	Yes
Lumens (lm)	1200 lm
Protection	IP20
Estimated life (h)	30.000
Diameter (cm)	17 cm
Suitable for sloped ceiling	No

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 11 November 2026