

Product sheet

Pronext Modular LED Spotlight 300W Salt-Resistant 4000K

Reference: LEDME GA6267



The iSG Lighting LED Modular Focus Pronext offers 300W with a Sanan source and 45,000 lumen luminance. Its light efficiency reaches 150 lm/W, operating between -40°C and 55°C at a beam angle of 90°. It has IP65, Ik8 protection and 50,000 hours of service life.

[View product online](#)

Description

The iSG Lighting Modular Led Pronext is a high-power industrial lighting system designed to deliver performance and durability in demanding environments. With a 45000 lumen light output, it ensures powerful and efficient lighting, ideal for applications that require high visibility.

Technical characteristics

- Watts: 300 w
- Light Source: Sanan
- Luminosity: 45000 lumens
- Efficiency Lm: 150
- Working temperature: -40°C ~ +55°C
- Angle: 90°
- Useful Life: 50000 hours
- Protection: IP65
- Ik: 8
- Class Electrical insulation: I
- Protection Against Overvoltage: 10 Kv
- Power supply: 100-265v ac
- Frequency: 50/60 Hz
- Installation: Area
- Material: Aluminium
- Driver: Philips

- Cri: 70
- Ugr: <26
- Ulr: 0% Assembly at 0o inclination
- Power Factor: 0.9
- Flicker Free: Yes
- Regulatory: 1-10V
- Guarantee: 7 years
- Color temperature: 2700K ?? 4000K ?? 5000K
- Replacement Light Source: Yes
- Replaceable Driver: Yes

Thanks to its construction in aluminium and polycarbonate, together with IP65 protection and IK8 certification, this device resists impacts and adverse conditions. The 1-10V regulation and the Philips driver ensure precise control of light without blinking, optimizing both energy efficiency and visual quality in industrial or commercial spaces.

Surface installation allows easy integration into ceilings or walls, facilitating maintenance thanks to replaceable components. Its wide range of working temperatures and voltage makes it versatile for various geographic locations and electrical networks.

Specifications

Appliance class	Class I
Frequency	50/60 Hz
Cri (Ra)	70
Driver included	Yes
EAN	8435579762677
Manufacturer	iSG Lighting
Lumens (lm)	45000 lm
Power (W)	300 W
Protection	IP65
Adjustable	Yes
Type of installation	Surface
Colour temperature	4000K
Estimated life (h)	50000
Suitable for sloped ceiling	No

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 13 October 2026