

Product sheet

Led Power Supply Lifud 150W 24Vdc Dimmable 0-10V

Brand: Lifud

Reference: LEDME LF-GAA150-625-24



Power supply led Lifud, 150W, 24Vdc, with regulation 0-10V, PWM and Rx. Stable output with power factor >0.9, overload and short circuit protection. Electrical insulation class II, IP20, impact resistant IK4. It works in temperature ranges from -20°C to +50°C. Design in PC material, surface installation.

[View product online](#)

Description

150W LED Lifud dimmable 0-10V CCT power supply with 24V DC output, designed to power LED systems with precise regulation. Compatible with 0-10V, PWM and Rx control signals, allowing continuous brightness adjustment. Ideal for controlled lighting applications in commercial or industrial environments.

Technical characteristics

- Maximum power: 150 W
- Power supply: 220-240 V AC
- Frequency: 50/60 Hz
- Output: 24 V DC
- Working temperature: -20°C ~ +50°C
- Protection: IP20
- Ik: 4 Kv
- Class Electrical insulation: II
- Overload Protection: Yes
- Short circuit protection: Yes
- Power Factor: >0.9
- Flicker Free: Yes
- Regulatory: 0-10V / PWM / Rx
- Material: PC

- Driver: Lifud
- Dimension: 360.8 x 42 x 30.3 mm
- Installation: Area
- Guarantee: 5 years

Specifications

Appliance class	Class II
Driver included	No
Manufacturer	Lifud
Weight (kg)	0,1 kg
Power (W)	150 W
Protection	IP20
Adjustable	Yes
Nominal voltage (V)	220-240 V AC
Type of installation	Surface
Suitable for sloped ceiling	No

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 8 October 2026