

Product sheet

Led Power Supply Lifud 75W 24Vdc Dimmable 0-10V

Brand: Lifud

Reference: LEDME LF-GDE075YV024



Power supply led Lifud, 75W, 24Vdc, with regulation 0-10V, PWM and Rx. Power supply 220-240V AC, 50/60 Hz. Electrical insulation class II, power factor > 0.9. IP20 protection, mechanical resistance IK4. It works in temperature ranges from -20°C to +50°C. Surface installation, polymer material PC. Includes protection against overload and short circuit.

[View product online](#)

Description

Power supply led Lifud dimmable 0-10V with 24V DC output, designed to power LED systems with precise regulation. Compatible with 0-10V, PWM and Rx control signals, allowing continuous brightness adjustment. Ideal for controlled lighting applications in commercial or residential environments.

Technical characteristics

- Maximum power: 75W
- Output: 24V DC
- Power supply: 220-240V AC
- Frequency: 50/60 Hz
- Working temperature: -20°C ~ +50°C
- Protection: IP20
- Ik: 4 Kv
- Class Electrical insulation: II
- Overload Protection: Yes
- Short circuit protection: Yes
- Power Factor: >0.9
- Flicker Free: Yes
- Regulatory: 0-10V/PWM/Rx
- Installation: Area

- Dimension: 299.5 x 42 x 30.3 mm
- Material: PC
- Driver: Lifud
- Guarantee: 5 years

Specifications

Appliance class	Class II
Manufacturer	Lifud
Power (W)	75W
Protection	IP20
Adjustable	Yes
Nominal voltage (V)	24V

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, [contact our support team](#)

Item downloaded on 9 October 2026