

Product sheet

Lifud 150W 24Vdc Adjustable DALI DT6 Power Supply

Brand: Lifud

Reference: LEDME LF-GSD150YV024B



Lifud 150W, 24VDC LED power supply, with DALI DT6 and Push regulation. Power supply 220-240V AC, 50/60 Hz. Electrical insulation class II, IP20 protection, IK4 mechanical strength. Power factor >0.9, flashless output (Flicker Free). Operating temperature -20°C to +50°C. Surface installation, polycarbonate material (PC). Protection against overload and short circuit.

[View product online](#)

Description

Dimmable led Lifud power supply with DALI DT6 or Push control, designed for LED lighting applications with stable 24V DC output. Maximum power of 150W, compatible with input voltages of 220-240V AC to 50/60 Hz. Ideal for industrial or commercial installations where precise light intensity regulation is required.

Technical characteristics

- Maximum power: 150 W
- Working temperature: -20°C ~ +50°C
- Protection: IP20
- Ik: 4 Kv
- Class Electrical insulation: II
- Overheating protection: no
- Overload Protection: Yes
- Short circuit protection: Yes
- Power supply: 220-240V AC
- Frequency: 50/60 Hz
- Output: 24V DC
- Installation: Area
- Dimension: 360.8 x 42 x 30.3 mm

- Material: PC
- Driver: Lifud
- Power Factor: >0.9
- Flicker Free: Yes
- Regulatory: DALI DT6/PUSH
- Guarantee: 5 years

Thanks to its regulation by DALI DT6 or Push, it allows the brightness to be adjusted accurately and efficiently in intelligent lighting systems. Its compact design and PC material make it suitable for environments with mechanical resistance requirements and basic protection.

Specifications

Appliance class	Class II
Manufacturer	Lifud
Power (W)	150W
Protection	IP20
Nominal voltage (V)	220-240V
Current type	DC
Type of installation	Surface
Suitable for sloped ceiling	No

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 9 October 2026