Product sheet



25W CCT Black Surface Circular Panel

Brand: LEDME

Reference: LEDME LM5592

The M LEDME 25W black circular surface panel integrates Smd 2835 light sources for a brightness of 2500 lumens and efficiency of 100 lm/W. Operates between -20°C and +45°C with 120° angle, 30000 hour life, IP20 protection and 170-265v power supply.

View product online

Description

M LEDME's Circular Black Surface Panel is an efficient lighting device designed to provide uniform and controllable light, ideal for applications where light accuracy is required without excessive glare.

Technical characteristics

- Mark: M LEDME
- Power: 25 W
- Light source: SMD 2835
- Luminosity: 2500 lm
- Light efficiency: 100 lm/W
- Working temperature: -20°C ~ +45°C
- Emission angle: 120°
- Lifetime: 30,000 hours
- Protection: IP20
- Electrical insulation class: II
- Power supply: 170-265 V AC
- Dimensions: 285x28 mm
- Body material: Aluminium
- chromatic reproduction index (CRI): 80
- UGR index: <19
- Guarantee: 3 years
- Color temperature options: 3 CST

Its low UGR index and high light efficiency ensure optimal performance in spaces that demand visual quality, while its aluminium construction ensures adequate thermal dissipation within the specified operating range.

Specifications

Appliance class	Class II
Bulb not included	No
Cap	LED
Cri (Ra)	80
Driver included	Yes
EAN	8435579755921
Manufacturer	Ledme
Lumens (lm)	2500 lm
Power (W)	25 W
Protection	IP20
Nominal voltage (V)	170-265
Current type	AC
Type of installation	Surface
Suitable for sloped ceiling	No

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 10 November 2026