

Product sheet

12V Flexilight LED Strip IP44 60 LEDs/m 20 meters Blue

Brand: LEDME

Reference: LEDME LM2726



20-meter flexible LED strip with Smd 2835 chips and a density of 60 LEDs per meter, delivering 810 lm/m brightness under 12V DC power. Features IP44 protection for outdoor use, a 120-degree emission angle, and an estimated lifespan of 30,000 hours of continuous operation.

[View product online](#)

Description

The M LEDME Flexilight LED strip is a 20-meter flexible lighting solution powered by 12V DC, designed to provide versatile and efficient illumination with a density of 60 LEDs per meter.

Technical Specifications

- Brand: M LEDME
- Power Supply: 12V DC
- Power: 9 W/m
- Technology: Smd 2835 Light Source
- Density: 60 LEDs/m
- Brightness: 810 lm/m
- Operating Temperature: -20°C ~ +45°C
- Emission Angle: 120°
- Lifespan: 30,000 hours
- Protection: IP44
- Insulation Class: III
- Material: PC
- CRI: 80
- Cut Interval: 5 cm
- Includes: Adhesive tape
- Flicker Free: Yes

- Dimmable: Yes
- Warranty: 3 years
- Available Color Temperatures: 2300K, 3000K, 4500K, 6000K and custom colors (Yellow, Blue, Gold, etc.)

Thanks to its high brightness and wide viewing angle, this strip provides uniform and bright illumination, ideal for highlighting indoor or outdoor spaces where precise color control without flickering is required.

Installation is easy thanks to the included adhesive tape, and the ability to cut every 5 cm allows you to adapt the exact length needed for any project, maintaining the electrical and aesthetic integrity of the system.

Specifications

Appliance class	Class III
Cri (Ra)	80
EAN	8435579727263
Manufacturer	Ledme
Halogen-free	Yes
Lumens (lm)	810 lm/m
Power (W)	9 W/m
Protection	IP44
Adjustable	Yes
Nominal voltage (V)	12V
Colour temperature	3000K
Estimated life (h)	30.000
Diameter (cm)	5 cm

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 30 September 2026