

Product sheet

LED Recessed Downlight 15W iSG Lighting 6000K Aluminum

Reference: LEDME GA4260



15W recessable Downlight with LED technology and Lifud driver, manufactured by iSG Lighting. It has Sanan source and emission of 1650 lumens at 6000K. Aluminium construction with 90° beam angle and 50000 hours service life. Operates between -20°C and +45°C under 220-240V AC power supply.

[View product online](#)

Description

The iSG Lighting's Downlight Led White Luxtar 15W is an recessable lighting device designed to deliver an efficient and durable light solution. With a power of 15 watts and a Sanan light source, it provides a brightness of 1650 lumens with an efficiency of 110 lm/W, ideal for spaces that require superior optical performance without consuming excess energy.

Technical characteristics

- Trademark: iSG Lighting
- Power: 15 W
- Light source: Sanan
- Lightness: 1650 lm
- Light efficiency: 110 lm/W
- Working temperature: -20°C ~ +45°C
- Beam angle: 90°
- Lifetime: 50,000 hours
- Protection: IP20, IK5
- Insulation class: II
- Overvoltage protection: 4 Kv
- Power supply: 220-240V AC
- Body material: Aluminium
- Driver: Lifud
- chromatic reproduction index (CRI): 80

- UGR: <19
- Power factor: 0.5
- Color temperature: 3000K ?? 6000K
- Regulatory: Optional
- Guarantee: 5 years
- Dimensions: 115x50H mm (cut: 100 mm)

Thanks to its aluminium construction and an angle of 90 degrees, this downlight ensures a uniform distribution of light with low glare (UGR <19), adapting to various interior lighting needs.

Specifications

Appliance class	Class II
Cri (Ra)	80
EAN	8435579742600
Manufacturer	iSG Lighting
Lumens (lm)	1650 lm
Power (W)	15 W
Protection	IP20
Colour temperature	3000K
Usage	Indoor

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 5 October 2026