

## Product sheet



## M LEDME Lounge LED Wall Light 10W 3000K

Brand: LEDME

Reference: LEDME LM6156

M LEDME's 10W Led Lounge Wall App offers a 920 lumen brightness with a color temperature of 3000K. Made of aluminium and polycarbonate, it features Sanan source, IP54 protection and 60 deg beam angle for efficient illumination.

[View product online](#)

### Description

The M LEDME Wall Led Lounge App is a surface lighting device designed to provide an efficient and durable light solution in various environments. Its robust construction ensures stable operation under variable conditions.

#### Technical characteristics

- Mark: M LEDME
- Power: 10 W
- Light source: Sanan
- Luminosity: 920 lumens
- Light efficiency: 92 lm/W
- Color temperature: 3000K
- chromatic reproduction index (CRI): 80
- Emission angle: 60°
- Lifetime: 30,000 hours
- Protection: IP54
- Electrical insulation class: I
- Power supply: 100-240V AC, 50/60 Hz
- Working temperature: -20°C ~ +45°C
- Material: Aluminium and PC
- Guarantee: 3 years
- Dimension: 67x50x180H mm

- Installation method: Area

Thanks to its high light efficiency and wide operating temperature range, this equipment provides constant and quality lighting. The IP54 protection and the IK8 certification ensure its resistance against dust, splashes and moderate blows, facilitating its maintenance in demanding spaces.

The surface installation allows a direct fixation on flat walls or ceilings without the need for additional complex structures, optimizing the available space.

Specifications

|                      |               |
|----------------------|---------------|
| Appliance class      | Class I       |
| Opening angle        | 60            |
| Cri (Ra)             | 80            |
| EAN                  | 8435579761564 |
| Manufacturer         | Ledme         |
| Lumens (lm)          | 920 lúmenes   |
| Power (W)            | 10 W          |
| Protection           | IP54          |
| Type of installation | Surface       |
| Colour temperature   | 3000K         |
| Estimated life (h)   | 30.000        |

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 8 October 2026