

Product sheet

**Pack of 2 units Bure Series LED Panel 60x60 cm 42W Philips Driver No Flicker 6000K**

Brand: LEDME

Reference: ---LEDME LM5381

M LEDME's LED Bure Series panel measures 60x60 cm with 42 W and Philips driver, offering 4200 lumens and 100 lm/W efficiency. It features Flicker Free, CRI 80, UGR <17 and 30,000-hour service life in IP40 aluminum housing.

[View product online](#)**Description**

The M LEDME's LED Bure Series Panel is an efficient 60x60 cm lighting system, designed to deliver even, blink-free light thanks to its Philips driver. With a power of 42W and a lumen of 4200 lumens, it guarantees optimal performance in various environments.

Technical characteristics

- Mark: M LEDME
- Power: 42 W
- Light source: Sanan
- Luminosity: 4200 lm
- Light efficiency: 100 lm/W
- Working temperature: -20°C ~ +45°C
- View angle: 120°
- Lifetime: 30,000 hours
- IP protection: IP40
- Electrical insulation class: II
- Power supply: 170-265V AC
- Dimensions: 595x595x35 mm
- Body material: Aluminium
- Driver: Philips
- chromatic reproduction index (CRI): 80

- Power factor: 0.9
- Flicker Free technology: Yes
- Available color temperatures: 3000K, 4500K, 6000K
- Guarantee: 5 years

Its aluminium construction and compact design allow a simple and durable installation, maintaining the thermal stability necessary to prolong the life of the internal components.

Specifications

Appliance class	Class II
High	35 mm
Width	60 cm
Cri (Ra)	80
EAN	8435579753811
Manufacturer	Ledme
Lumens (lm)	4200 lm
Material	Aluminio
Power (W)	42 W
Protection	IP40
Reference	LEDME LM5381
Adjustable	No
Nominal voltage (V)	170-265 V
Colour temperature	6000K
Estimated life (h)	30.000
Suitable for sloped ceiling	No

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 27 September 2026