

Product sheet

Mean Well XLG-50-A 50 W IP67 Driver

Brand: MEAN WELL

Reference: LEDME XLG-50-A



Driver Meanwell Xlg-50-A, AC 100-305 V power supply, DC 22-54 V output at 1000 mA. Maximum power of 50 W, power factor 0.95. IP67 protection, resistant to working temperatures between -40°C and +90°C. Aluminium design for efficient thermal dissipation. It does not include overheating protection.

[View product online](#)

Description

Driver Meanwell Xlg-50-A designed for LED modular retrofitting applications, offers stable and efficient power supply for LED spotlights. Compatible with modular lighting systems, it ensures continuous operation in extreme conditions thanks to its wide operating temperature range.

Technical characteristics

- Maximum power: 50 W
- Working temperature: -40°C ~ +90°C
- Protection: IP67
- Overvoltage protection: 6 kV
- Overheating protection: no
- Power supply: 100-305 V AC
- Departure: 22-54 V DC
- Current Intensity: 1000 mA
- Dimension: 105 x 63 x 30 mm
- Material: Aluminium
- Power Factor: 0.95
- Guarantee: 5 years

This driver is suitable for industrial or outdoor installations where high resistance to adverse environmental conditions is required, thanks to its IP67 protection and wide thermal range.

Specifications

Rated current (A)	1
Width	63 mm
Manufacturer	MEAN WELL
Long	105 mm
Halogen-free	Yes
Power (W)	50 W
Depth	30 mm
Protection	IP67 - uso esterno
Nominal voltage (V)	100-305V AC

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 11 October 2026