Product sheet



Slim Series Circular LED Panel 20W Pack 2 4500K

Brand: LEDME

Reference: LEDME LM5552

Recessed Slim Series circular LED panel, 20W, with aluminum housing and SMD 2835 driver. Delivers 2000 lumens, 120-degree beam angle, and 4500K color temperature. Features a 30,000-hour lifespan, CRI of 80, and IP20 protection. Operates on 170-265V AC input within an ambient temperature range of -20 to 45°C.

View product online

Description

The M LEDME Slim Series Circular LED Panel is a high-efficiency recessed lighting system designed to provide uniform and durable illumination for various indoor environments.

Technical Specifications

- Brand: M LEDME
- Power: 20 W
- Technology: SMD 2835 Light Source
- Luminous Flux: 2000 lm
- Efficacy: 100 lm/W
- Operating Temperature: -20°C ~ +45°C
- Beam Angle: 120°
- Lifespan: 30,000 hours
- Protection: IP20, IK5
- Input Voltage: 170-265V AC
- Material: Aluminum
- CRI: 80
- Warranty: 3 years
- Dimensions: 220x10H mm (Cutout: 200 mm)

Thanks to its aluminum housing and high luminous efficacy, this panel ensures optimal performance and

a long operational life.

The installation is recessed, requiring a 200 mm cutout for integration into false ceilings or existing structures.

Specifications

Memory	No
High	10H mm
Width	220
Opening angle	120°
Diameter embedment (mm)	200 mm
Driver included	Yes
EAN	8435579755525
Manufacturer	Ledme
Intensity	20
Long	10H mm
Halogen-free	Yes
Lumens (lm)	2000 lm
Material	Aluminio
Measures	220x10H mm
Battery included	No
Power (W)	20 W
Maximum power (W)	20 W
Depth	10H mm
Protection	IP20
Adjustable	No
Nominal voltage (V)	170-265 V
Estimated life (h)	30.000
Light power (W)	20
Usage	Indoor

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 28 November 2026