Product sheet



Slim M Circular Surface Panel LEDME 5W 6000K

Brand: LEDME

Reference: LEDME LM5564

M LEDME Slim Series Circular Surface Panel integrates Smd 2835 technology with 5W power and 500 lumens. Its aluminium housing efficiently dissipates heat under working temperatures between -20°C and +45°C. With a beam angle of 120° and CRI of 80°, it offers uniform lighting.

View product online

Description

The Slim Series Circular Surface Panel of the M LEDME brand is a lighting device designed to provide efficient lighting with a thin profile and circular finish. Its aluminium construction ensures adequate thermal dissipation, ensuring stable operation within the specified working temperature range.

Technical characteristics

- Mark: M LEDME
- Power: 5 w
- Light Source: Smd 2835
- Luminosity: 500 lm
- Efficiency Lm: 100
- Working temperature: -20°C ~ +45°C
- Emission angle: 120°
- Useful Life: 30000 hours
- Protection: IP20
- Class Electrical insulation: II
- Power supply: 170-265v ac
- Dimension: 80X28H mm
- Materials: Aluminium
- CRI: 80
- Guarantee: 3 years

- Color Temperature: 3000K, 4500K or 6000K

The high light efficiency and the chromatic reproduction index of 80 allow for clear and faithful colour illumination, adapting to various visual needs without requiring complex installations due to their IP20 degree of protection.

Specifications

Appliance class	Class II
Opening angle	120°
Cri (Ra)	80
EAN	8435579755648
Manufacturer	Ledme
Lumens (lm)	500 lm
Material	Aluminio
Measures	80X28H mm
Power (W)	5 W
Protection	IP20
Type of installation	Surface
Type of lamp	LED SMD 2835
Colour temperature	6000K
Estimated life (h)	30000

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 11 November 2026