Product sheet



Slim M Circular Surface Panel LEDME 5W 3000K

Brand: LEDME

Reference: LEDME LM5566

Slim circular surface panel of the M LEDME brand with 5W power and color temperature of 3000K. It incorporates Smd 2835 light source, offering a brightness of 500 lumens and efficiency of 100 lm/W. It has a beam angle of 120°, a shelf life of 30000 hours and IP20 protection.

View product online

Description

The Slim Series Circular Surface Panel from M LEDME is an efficient lighting device designed to deliver a compact and durable light solution. Its aluminium construction guarantees thermal stability and mechanical resistance, while its low profile discreetly integrates it into various spaces.

Technical characteristics

- Mark: M LEDME
- Power: 5 W
- Light source technology: SMD 2835
- Luminosity: 500 lm
- Light efficiency: 100 lm/W
- Working temperature: -20°C ~ +45°C
- Emission angle: 120°
- Lifetime: 30,000 hours
- Protection: IP20
- Electrical insulation class: II
- Power supply: 170-265 V AC
- Dimensions: 80 x 28 mm (high)
- Materials: Aluminium housing
- chromatic reproduction index (CRI): 80
- Color temperature options: 3000K, 4500K and 6000K

- Guarantee: 3 years

Thanks to its high energy efficiency and wide input voltage range, this panel provides consistent and reliable lighting. The combination of an 80 CRI and multiple color temperatures allows light to be adapted to different visual needs without compromising system performance.

Specifications

Appliance class	Class II
High	28 mm
Cri (Ra)	80
EAN	8435579755662
Manufacturer	Ledme
Lumens (lm)	500 lm
Material	Aluminio
Power (W)	5 W
Protection	IP20
Type of lamp	LED SMD 2835
Colour temperature	3000K
Estimated life (h)	30000

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 11 November 2026