

Product sheet

**Adjustable LED Downlight
Cobfix 10W M LEDME 900lm
6000K**

Brand: LEDME

Reference: LEDME GA4404

M LEDME's Focus Downlight LED Orientable Cobfix integrates Bridgelux source and Lifud driver for reliable performance.

[View product online](#)**Description**

The Focus Downlight Led Orientable Cobfix from M LEDME is an efficient lighting device designed to provide directional light with high quality LED technology.

Technical characteristics

- Mark: M LEDME
- Power: 10 W
- Light source: Bridgelux
- Luminosity: 900 lm
- Light efficiency: 90 lm/W
- Color temperature: 3000K or 4500K
- chromatic reproduction index (CRI): 80
- Beam angle: 36°
- Lifetime: 30,000 hours
- Body material: Aluminium
- Driver: Lifud
- IP protection: IP20
- Insulation class: II
- Overvoltage protection: 4 kV
- Power supply: 170-265 V AC
- Dimensions: 85x50 mm (H)
- Cutting dimension: 75 mm

- Power factor: 0.6
- Guarantee: 5 years
- Operating temperature range: -20°C to +45°C

Its aluminium construction and the Bridgelux fountain ensure a stable and durable luminous performance over time.

The adjustable orientation allows to direct the light exactly where it is required, optimizing the lighting of the space without wasting energy.

Specifications

Appliance class	Class II
Opening angle	36°
Cri (Ra)	80
Diameter embedment (mm)	75 mm
EAN	8435579744048
Manufacturer	Ledme
Lumens (lm)	900 lm
Material	Aluminio
Power (W)	10 W
Protection	IP20
Nominal voltage (V)	170-265 V
Colour temperature	3000K
Estimated life (h)	30.000

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 30 September 2026