

Product sheet

**M LEDME 10W 3000K
Adjustable LED Downlight**

Brand: LEDME

Reference: LEDME GA4406



The 10W Downlight Led Orientable Cobfix focus integrates the Bridgelux light source and Lifud driver to ensure stable optical performance. With a brightness of 900 lumens and 90 lm/W efficiency, it offers a 36° adjustable beam angle.

[View product online](#)**Description**

The Focus Downlight Led Orientable Cobfix by M LEDME is an efficient lighting device designed for indoor spaces requiring directional and adjustable light. Its aluminium construction ensures adequate thermal dissipation, while its Bridgelux source ensures a constant luminous performance.

Technical characteristics

- Mark: M LEDME
- Power: 10 W
- Light Source: Bridgelux
- Luminosity: 900 lm
- Efficiency: 90 lm/W
- Working temperature: -20°C ~ +45°C
- Beam angle: 36°
- Lifetime: 30,000 hours
- Protection: IP20
- Insulation class: II
- Overvoltage protection: 4 Kv
- Power supply: 170-265V ac
- Dimensions: 85x50H mm
- Cutting dimension: 75 mm
- Material: Aluminium
- Driver: Lifud

- CRI: 80
- Power factor: 0.6
- Guarantee: 5 years
- Color temperature: 3000K ?? 4500K

Given its narrow 36° beam and high efficiency, this focus is suitable for highlighting specific architectural elements or providing focused lighting in work areas where visual accuracy is required without excessive glare.

Specifications

Appliance class	Class II
Opening angle	36°
Cri (Ra)	80
Diameter embedment (mm)	75 mm
EAN	8435579744062
Manufacturer	Ledme
Lumens (lm)	900 lm
Material	Aluminio
Measures	85x50H mm
Power (W)	10 W
Protection	IP20
Nominal voltage (V)	170-265V AC
Colour temperature	3000K
Estimated life (h)	30.000
Usage	Indoor

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 1 October 2026