Product sheet



Surface Panel Circular Series Pro 20W M LEDME

Brand: LEDME

Reference: LEDME GA5644

The Series Pro Surface Mount Circular panel from M LEDME integrates SMD 2835 source and Lifud driver for efficient lighting. With 20W, it offers 2000 lumens and CRI 80 at a color temperature of 4000K.

View product online

Description

The Series Pro Surface Mount Circular Panel from M LEDME is a 20W lighting device designed to offer performance and durability in indoor spaces, available in color temperatures of 3000K, 4000K, and 6000K.

Technical Specifications

- Light Source: SMD 2835
- Luminous Flux: 2000 lm
- Efficiency: 100 lm/W
- Operating Temperature: -20°C ~ +45°C
- Beam Angle: 120°
- Lifespan: 30,000 hours
- Protection: IP20, IK5
- Insulation Class: II
- Surge Protection: 4 Kv
- Input: 170-265V AC
- Output: 25-40V DC, 450 mA
- Dimensions: 210x28H mm
- Material: Aluminum
- Driver: Lifud
- CRI: 80
- Power Factor: 0.5

- Warranty: 5 years

With an aluminum construction and a Lifud driver, this panel ensures stable operation within a wide thermal range, guaranteeing a prolonged lifespan of up to 30 thousand hours without the need for frequent maintenance.

Specifications

Appliance class	Class II
Opening angle	120°
Cri (Ra)	80
EAN	8435579756447
Manufacturer	Ledme
Lumens (lm)	2000 lm
Material	Aluminio
Protection	IP20
Nominal voltage (V)	170-265V
Type of installation	Surface
Type of lamp	LED SMD 2835
Colour temperature	4000K
Estimated life (h)	30000
Usage	Indoor

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 10 November 2026