Product sheet



Surface Mount Circular Panel Pro Series 20W - Dsc 3000k

Brand: LEDME

Reference: LEDME GA5645

M LEDME Pro Series circular surface panel with 20W and SMD 2835 font. It offers 2000 lumens, 100 lm/W efficiency and 120° angle. It works between -20°C and 45°C with a 30000-hour service life, powered by 170-265V AC.

View product online

Description

The M LEDME Pro Circular Series Surface Panel is a lighting device designed to deliver an efficient and durable solution, integrating advanced LED technology into a compact format.

Technical characteristics

- Watts: 20 w
- Light Source: Smd 2835
- Luminosity: 2000 lm
- Efficiency Lm: 100
- Working temperature: -20°C ~ +45°C
- Emission angle: 120°
- Useful Life: 30000 hours
- Protection: IP20
- Ik: 5
- Class Electrical insulation: II
- Overvoltage protection: 4 Kv
- Power supply: 170-265v ac
- Departure: 25-40V DC
- Current Intensity: 450 mA
- Dimension: 210X28H mm
- Material: Aluminium
- Driver: Lifud

- CRI: 80
- Power Factor: 0.5
- Guarantee: 5 years
- Color Temperature: 3000K, 4000K or 6000K

With its aluminium construction and a quality Lifud driver, this panel ensures stable performance under various thermal conditions, ensuring a long service life without compromising light quality.

Specifications

Appliance class	Class II
Cri (Ra)	80
Driver included	Yes
EAN	8435579756454
Manufacturer	Ledme
Lumens (lm)	2000 lm
Material	Aluminio
Measures	210x28 mm
Protection	IP20
Type of installation	Surface
Type of lamp	LED SMD 2835
Colour temperature	3000K
Estimated life (h)	30000

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 11 November 2026