

Product sheet



LED Wall Light Dynamic CCT 12W brand M LEDME

Brand: LEDME

Reference: LEDME LM6117

M LEDME's Led Dynamic Cct Wall App is a lighting device with CCT technology and Lumileds source. It operates at 12 watts, offering a brightness of 840 lumens and an efficiency of 70 lm/W. It has IP65 protection, 180 degree angle and 30000 hours service life.

[View product online](#)

Description

The M LEDME Wall Led Dynamic CCT is a lighting device designed to deliver chromatic versatility and energy efficiency in indoor spaces. Its technology allows to adjust the color temperature through three different configurations, adapting to different atmospheric needs without requiring physical changes in the equipment.

Technical characteristics

- Watts: 12 w
- Light Source: Lumileds
- Luminosity: 840 lm
- Efficiency Lm: 70 lm/w
- Working temperature: -20°C ~ +45°C
- Emission angle: 180°
- Useful Life: 30000 hours
- Protection: IP65
- Ik: 8
- Class Electrical insulation: I
- Power supply: 175-265v ac
- Frequency: 50/60 Hz
- Installation: Area
- Dimension: 170X170X95H mm
- Material: Aluminium

- CRI: 80
- Guarantee: 3 years
- Color Temperature: 3CCT

The robust aluminium and polycarbonate housing ensures efficient thermal dissipation, extending the life of the component. Its degree of protection IP65 makes it suitable for areas at risk of moderate or protected outdoor splashes. With a chromatic reproduction index of 80, the colours are presented with fidelity and naturalness.

Surface installation facilitates mounting on vertical or horizontal walls using standard tools. Its wide voltage range (175-265V) ensures stable operation in variable electrical networks without the need for additional transformers, simplifying integration into residential or commercial projects.

Specifications

Appliance class	Class I
Frequency	50/60 Hz
Cri (Ra)	80
EAN	8435579761175
Manufacturer	Ledme
Lumens (lm)	840 lm
Measures	170x170x95 mm
Power (W)	12 W
Protection	IP65
Nominal voltage (V)	175-265 V
Type of installation	Surface
Estimated life (h)	30000

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 13 October 2026