Product sheet



Circular Surface Panel Nickel 25W CCT M LEDME

Brand: LEDME

Reference: LEDME LM5546

M LEDME circular surface panel with nickel finish and SMD LED technology. Operates at 25 watts with a luminance of 2500 lumens and efficiency of 100 lm/W. It has a beam angle of 120 deg, 30000 hours service life and IP44 protection for use in wet interiors.

View product online

Description

M LEDME's 25W Cct Circular Nickel Surface Panel is a lighting device designed to provide an efficient and durable light solution. Its aluminium construction ensures robustness, while its IP44 protection makes it suitable for environments with some exposure to moisture or dust.

Technical characteristics

- Mark: M LEDME
- Power: 25 w
- Technology: Light Source Smd Led
- Lightness: 2500 lumens
- Efficiency: 100 lm/w
- Emission angle: 120°
- Useful Life: 30000 hours
- Protection: IP44
- Power supply: 170-265v ac
- Dimensions: 285X28H mm
- Material: Aluminium
- CRI: 80
- Guarantee: 3 years
- Color temperature range: 3CCT

Thanks to its high chromatic reproduction rate and long service life, this panel maintains a stable optical

performance for decades, offering uniform lighting thanks to its wide distribution angle.

Specifications

Colour	Níquel
Cri (Ra)	80
EAN	8435579755464
Manufacturer	Ledme
Lumens (lm)	2500 lm
Material	Aluminio
Power (W)	25 W
Protection	IP44
Type of installation	Surface
Estimated life (h)	30000
Usage	Indoor

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 14 November 2026