Product sheet



Slim Circular Surface Panel 20W 6000K LEDME

Brand: LEDME

Reference: LEDME LM5243

M LEDME's Slim circular surface panel integrates Smd 2835 diodes to provide 2000 lumens with 100 lm/W efficiency. Its aluminium housing dissipates heat in a range of -20°C to +45°C, ensuring a shelf life of 30000 hours under power supply of 170-265v ac.

View product online

Description

The Slim Series Circular Surface Panel by M LEDME is a lighting device designed to be integrated into roofs by surface installation, offering an efficient and compact light solution.

Technical characteristics

- Mark: M LEDME
- Power: 20 W
- Light source: Smd 2835
- Luminosity: 2000 lm
- Light efficiency: 100 lm/W
- Working temperature: -20°C ~ +45°C
- Emission angle: 120°
- Lifetime: 30,000 hours
- Protection: IP20
- Electrical insulation class: II
- Power supply: 170-265V ac
- Material: Aluminium
- CRI: 80
- Guarantee: 3 years
- Available color temperature: 3000K, 4500K, 6000K
- Dimensions: 210x28 mm

Thanks to its aluminium construction and high energy efficiency, this panel ensures stable optical performance for decades of continuous use.

Specifications

Appliance class	Class II
Opening angle	120°
Cri (Ra)	80
EAN	8435579752432
Manufacturer	Ledme
Lumens (lm)	2000 lm
Material	Aluminio
Measures	210x28 mm
Protection	IP20
Nominal voltage (V)	170-265V AC
Type of installation	Surface
Type of lamp	LED SMD 2835
Colour temperature	6000K
Estimated life (h)	30000

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 7 November 2026