Product sheet



Dial 36W M LEDME Circular Ceiling Light 3000lm 6000K IP20

Brand: LEDME

Reference: LEDME LM8201

Circular LED Plaster 36W and 6000K dial of the M LEDME brand, designed for efficient lighting with Epistar source. It offers a brightness of 3000 lumens and efficiency of 83 lm/W. It has 180° beam angle, 30,000-hour service life and IP20 protection.

View product online

Description

The Circular LED Plaster 36W Dial is an efficient light solution designed to provide uniform and durable lighting in various interior spaces. Its integrated LED technology ensures optimal performance with low energy consumption.

Technical characteristics

- Mark: M LEDME
- Power: 36W
- Light source: Epistar
- Luminosity: 3000 lumens
- Light efficiency: 83 lm/W
- Emission angle: 180°
- Lifetime: 30,000 hours
- Protection: IP20
- Power supply: 170-265V AC
- Dimensions: 390x65mm
- Material: PC (Polycarbonate)
- chromatic reproduction index (CRI): 80
- Guarantee: 3 years
- Available color temperatures: 4500K and 6000K

Thanks to its high light efficiency and wide emission angle, this device provides comprehensive and uniform lighting, ideal for lighting large surfaces with a single point of light.

Specifications

Cri (Ra)	80
Manufacturer	Ledme
Lumens (lm)	3000 lm
Material	PC
Measures	390x65mm
Power (W)	36W
Protection	IP20
Nominal voltage (V)	170-265V
Colour temperature	6000K
Usage	Indoor

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 21 November 2026