

Product sheet

LED Ceiling Dial 36W 4500K Brand M LEDME

Brand: LEDME

Reference: LEDME LM8202



Circular LED Plaster M LEDME dial with 36W power and adjustable color temperature between 4500K and 6000K. It incorporates Epistar light source, efficiency of 83 lumens per watt and 180 degree emission angle.

[View product online](#)

Description

M LEDME's Circular LED Plaster Dial is an efficient and modern lighting solution designed to deliver optimum luminous performance with reduced energy consumption. Its construction in polycarbonate (PC) guarantees durability, while its light source Epistar ensures a stable and reliable operation over time.

Technical characteristics

- Mark: M LEDME
- Power: 36 W
- Light source: Epistar
- Luminosity: 3000 lumens
- Luminous efficacy: 83 lm/W
- Emission angle: 180°
- Lifetime: 30,000 hours
- Protection: IP20
- Power supply: 170-265V AC
- Dimensions: 390x65 mm
- Material: PC
- chromatic reproduction index (CRI): 80
- Guarantee: 3 years
- Color temperature: 4500K or 6000K

Thanks to its high light efficiency and wide distribution angle, this device provides a uniform and bright lighting, ideal for spaces that require visual clarity without generating excessive glare.

Specifications

Cri (Ra)	80
Manufacturer	Ledme
Lumens (lm)	3000 lm
Material	PC
Measures	390x65 mm
Power (W)	36 W
Protection	IP20
Nominal voltage (V)	170-265V
Colour temperature	4500K

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 5 October 2026