Product sheet



M LEDME Dial Circular LED Ceiling Light 24W 6500K

Brand: LEDME

Reference: LEDME LM8204

Circular LED Plaster 24W Dial with color temperature 6500K and Epistar light source. It offers a brightness of 2000 lumens, 83 lm/W efficiency and 180° emission angle. It has a shelf life of 30000 hours, IP20 protection, 80 CRI index and 340x65 mm dimensions for surface installation.

View product online

Description

M LEDME’s Circular LED Plaster Dial is a surface lighting device designed to provide an efficient and durable light source in various interior environments.

Technical characteristics

- Watts: 24 w
- Light Source: Epistar
- Luminosity: 2000 lm
- Efficiency Lm: 83
- Emission angle: 180°
- Useful Life: 30000 hours
- Protection: IP20
- Power supply: 170-265v ac
- Installation: Area
- Dimension: 340X65 mm
- Material: PC
- CRI: 80
- Guarantee: 3 years
- Color temperature: 4500K ?? 6000K

By providing a high rate of chromatic reproduction and extended service life, this model ensures

consistent optical performance over time.

Specifications

Opening angle	180°
Cri (Ra)	80
Manufacturer	Ledme
Lumens (lm)	2000 lm
Material	PC
Measures	340x65 mm
Power (W)	24 W
Protection	IP20
Nominal voltage (V)	170-265 V
Type of installation	Surface
Colour temperature	6500K
Estimated life (h)	30000

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 28 November 2026