

Product sheet

M LEDME Dial Circular LED Ceiling Light 24W 4500K

Brand: LEDME

Reference: LEDME LM8205



M LEDME Dial circular ceiling light with 24W power and 4500K color temperature. Features Epistar light source, delivering 2000 lumens with 83 lm/W efficiency. Offers a 180° emission angle, 30,000-hour lifespan, and IP20 protection for surface mounting.

[View product online](#)

Description

The M LEDME Dial circular ceiling light is a surface-mounted lighting device designed to provide an efficient and durable lighting solution, available in 4500K and 6000K color temperatures.

Technical Specifications

- Brand: M LEDME
- Power: 24W
- Light Source: Epistar
- Luminous Flux: 2000 lm
- Efficiency: 83 lm/W
- Emission Angle: 180°
- Lifespan: 30,000 hours
- Protection: IP20
- Supply Voltage: 170-265V AC
- Installation: Surface
- Dimensions: 340x65 mm
- Material: PC
- CRI: 80
- Warranty: 3 years

By combining high luminous efficiency with an Epistar chip source and a Color Rendering Index (CRI) of 80, this ceiling light ensures superior optical performance and appropriate color stability for spaces

requiring visual clarity.

Specifications

Opening angle	180°
Cri (Ra)	80
Manufacturer	Ledme
Lumens (lm)	2000 lm
Material	PC
Measures	340x65 mm
Power (W)	24 W
Protection	IP20
Nominal voltage (V)	170-265 V
Type of installation	Surface
Colour temperature	4500K
Estimated life (h)	30000

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 4 October 2026