

Product sheet

Circular Slim Series LED Panel 12W 4500K M LEDME

Brand: LEDME

Reference: LEDME LM5208



M LEDME Slim Series Circular LED panel integrates Smd 2835 light source to deliver 1200 lumens with 100 lm/W efficiency. Its aluminium housing allows recessable installation in spaces of 170 mm in diameter, operating between -20°C and +45°C at a beam angle of 120°.

[View product online](#)

Description

M LEDME's Slim Series Led Circular Panel is an recessable lighting device designed to deliver efficient and durable light in indoor spaces.

Technical characteristics

- Watts: 12 w
- Light Source: Smd 2835
- Lightness: 1200 lm
- Efficiency Lm: 100 lm/w
- Working temperature: -20°C ~ +45°C
- Emission angle: 120°
- Useful Life: 30000 hours
- Protection: IP20
- Protection class IK: 5
- Power supply: 170-265v ac
- Body material: Aluminium
- chromatic reproduction index (CRI): 80
- Guarantee: 3 years
- Available color temperatures: 3000K, 4500K, 6000K
- External dimensions: 170x10H mm
- Cutting dimension: 150 mm

Its aluminium construction and wide working temperature range ensure stable operation under various environmental conditions.

Specifications

High	10 mm
Cri (Ra)	80
Diameter	170 mm
Manufacturer	Ledme
Lumens (lm)	1200 lm
Material	Aluminio
Power (W)	12 W
Protection	IP20
Nominal voltage (V)	170-265 V
Type of lamp	LED SMD 2835
Colour temperature	4500K
Estimated life (h)	30000

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 3 October 2026