

Product sheet

M LEDME Slim Series Circular LED Panel 25W 4500k

Brand: LEDME

Reference: LEDME LM5214



The M LEDME Slim Series circular LED panel integrates SMD 2835 sources with 25W and 2500 lumens, offering an efficiency of 100 lm/W. Its aluminum housing allows recessed installation with a cutout dimension of 280 mm.

[View product online](#)

Description

The M LEDME Slim Series Circular LED Panel is a recessed lighting device designed to provide an efficient and durable lighting solution. With a power of 25W and a luminosity of 2500 lumens, this panel uses SMD 2835 technology to ensure optimal performance in various environments.

Technical Specifications

- Brand: M LEDME
- Power: 25 w
- Luminous Source: Smd 2835
- Luminosity: 2500 lumens
- Efficiency: 100 lm/w
- Operating Temperature: -20°C ~ +45°C
- Emission Angle: 120°
- Lifespan: 30000 hours
- Protection: IP20
- Electrical Insulation Class: II
- Supply: 170-265v ac
- Material: Aluminum
- CRI: 80
- Warranty: 3 years
- Available Color Temperatures: 3000K, 4000K, 6000K
- Dimensions: 295x10H mm (cutout: 280 mm)

Thanks to its aluminum construction and high luminous efficiency, this panel provides uniform and quality lighting. Its wide range of color temperatures allows adaptation to different aesthetic or functional needs, while its robust lifespan ensures reduced maintenance over time.

The installation is recessed, facilitating its integration into flat ceilings. The compact design and low profile of 10 mm height contribute to a clean and modern aesthetic in any space where it is installed.

Specifications

Appliance class	Class II
Opening angle	120°
Cri (Ra)	80
EAN	8435579752142
Manufacturer	Ledme
Lumens (lm)	2500 lm
Material	Aluminio
Measures	295X10H mm
Power (W)	25 W
Protection	IP20
Nominal voltage (V)	170-265 V
Type of lamp	LED SMD 2835
Estimated life (h)	30000

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 29 September 2026