Product sheet



Slim Surface Panel Square Series 25W 4500K

Brand: LEDME

Reference: LEDME LM5257

The M LEDME Slim Square Surface Panel integrates Smd 2835 source with 25W and luminance of 2500 lm. Its luminous efficiency reaches 100 lm/W, offering a 120° angle and a lifespan of 30000 hours under 4500K color temperature.

View product online

Description

The M LEDME Slim Square Surface Panel Series is an efficient lighting device designed to provide uniform and controlled light in indoor spaces, offering color temperature options of 3000K, 4500K, and 6000K.

Technical Specifications

- Brand: M LEDME
- Power: 25 W
- Light Source: Smd 2835
- Luminous Flux: 2500 lm
- Luminous Efficiency: 100 lm/W
- Operating Temperature: -20°C ~ +45°C
- Emission Angle: 120°
- Lifespan: 30000 hours
- Protection Rating: IP20
- Insulation Class: IK5
- Supply Voltage: 170-265V ac
- Dimensions: 285x28H mm
- Body Material: Aluminum
- Color Rendering Index (CRI): 80
- Warranty: 3 years

Its aluminum construction and wide operating temperature range ensure stable and durable operation, while high luminous efficiency guarantees optimal performance with low energy consumption.

Specifications

Opening angle	120°
Cri (Ra)	80
EAN	8435579752579
Manufacturer	Ledme
Lumens (lm)	2500 lm
Material	Aluminio
Measures	285x28H mm
Power (W)	25 W
Protection	IP20
Nominal voltage (V)	170-265V
Type of installation	Surface
Type of lamp	LED SMD 2835
Colour temperature	4500K
Estimated life (h)	30000

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 10 November 2026