Product sheet



Slim Circular Surface Panel 6W 6000K LEDME

Brand: LEDME

Reference: LEDME LM5289

M LEDME-branded Slim circular surface panel with 6W power and 6000K color temperature. It uses Smd 2835 light source to achieve a brightness of 600 lumens and efficiency of 100 lm/W. It has a beam angle of 120°, 30000 hours service life, aluminium material and IP20 protection.

View product online

Description

The Slim Series Circular Surface Panel from M LEDME is a surface lighting device designed to provide an efficient and compact light solution, available at color temperatures 3000K, 4500K and 6000K.

Technical characteristics

- Mark: M LEDME
- Watts: 6 w
- Light Source: Smd 2835
- Lightness: 600
- Efficiency Lm: 100
- Working temperature: -20°C ~ +45°C
- Angle: 120°
- Useful Life: 30000
- Protection: IP20
- Ik: 5
- Class Electrical insulation: II
- Power supply: 170-265v ac
- Installation: Area
- Dimension: 120X28H mm
- Material: Aluminium
- Cri: 80

- Guarantee: 3

With its aluminium construction and 120° emission angle, this panel ensures adequate thermal dissipation and wide light distribution, ensuring optimum performance during its long service life of 30,000 hours.

Specifications

Appliance class	Class II
High	28 mm
Cri (Ra)	80
Diameter	120 mm
EAN	8435579752890
Manufacturer	Ledme
Lumens (lm)	600 lm
Material	Aluminio
Power (W)	6 W
Protection	IP20
Type of installation	Surface
Type of lamp	LED SMD 2835
Colour temperature	6000K
Estimated life (h)	30000

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 7 November 2026