Product sheet



# Slim M Round Surface Panel LEDME 25W Aluminum 3000K 4500K 6000K

Brand: LEDME

Reference: LEDME LM5247

The Slim circular surface panel from M LEDME integrates Smd 2835 technology to deliver 2500 lumens with a luminous efficacy of 100 lm/W. Its aluminum design allows an operating temperature range between -20°C and +45°C, ensuring a lifespan of 30000 hours under universal power supply of 170-265v ac.

**View product online**

## Description

The M LEDME Slim Circular Surface Panel is an efficient lighting device designed to offer a compact and durable lighting solution, available in color temperatures of 3000K, 4500K, and 6000K.

Technical Specifications

- Brand: M LEDME
- Power: 25 w
- Light source: Smd 2835
- Luminosity: 2500
- Luminous efficacy: 100 lm/w
- Operating temperature: -20°C ~ +45°C
- Beam angle: 120°
- Lifespan: 30000 hours
- Protection: IP20
- Electrical insulation class: II
- Power supply: 170-265v ac
- Dimensions: 285X28H mm
- Body material: Aluminum
- Color Rendering Index (CRI): 80
- Warranty: 3 years

Thanks to its aluminum construction and high luminous efficacy, this panel guarantees optimal performance and long operational life in various environments.

## Specifications

| | |
|---|---|
| Appliance class | Class II |
| Cri (Ra) | 80 |
| EAN | 8435579752470 |
| Manufacturer | Ledme |
| Lumens (lm) | 2500 lm |
| Material | Aluminio |
| Measures | 285x28H mm |
| Power (W) | 25 W |
| Protection | IP20 |
| Type of installation | Surface |
| Type of lamp | LED SMD 2835 |
| Colour temperature | 3000K |
| Estimated life (h) | 30000 |

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 14 November 2026