Product sheet



Slim Surface Circular LEDME Panel 25W 3000K

Brand: LEDME

Reference: LEDME LM5248

Slim series circular surface panel from M LEDME with 25W power and 3000K color temperature. Uses SMD 2835 diodes to achieve 2500 lumens luminance and a 120-degree beam angle.

View product online

Description

The M LEDME Slim Series Circular Surface Panel is an efficient lighting device designed to offer a compact and durable lighting solution, ideal for spaces requiring low energy consumption and high light quality.

Technical Specifications

- Brand: M LEDME
- Power: 25 W
- Light Source: Smd 2835
- Luminous Flux: 2500 lm
- Luminous Efficacy: 100 lm/W
- Operating Temperature: -20°C ~ +45°C
- Emission Angle: 120°
- Lifespan: 30000 hours
- Protection: IP20
- Electrical Insulation Class: II
- Supply Voltage: 170-265V ac
- Dimensions: 285x28H mm
- Material: Aluminum
- Color Rendering Index (CRI): 80
- Warranty: 3 years
- Color Temperature Options: 3000K, 4500K, 6000K

Thanks to its aluminum construction and high luminous efficiency, this panel guarantees optimal performance while maintaining wide operating temperatures and faithful color rendering.

Specifications

Appliance class	Class II
Cri (Ra)	80
EAN	8435579752487
Manufacturer	Ledme
Lumens (lm)	2500 lm
Material	Aluminio
Power (W)	25 W
Protection	IP20
Nominal voltage (V)	170-265V AC
Type of installation	Surface
Type of lamp	LED SMD 2835
Colour temperature	3000K
Estimated life (h)	30000

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 6 November 2026