Product sheet

Bure Series Rectangular LED Panel 120x60 cm 80W No Flicker 4500K

Brand: LEDME

Reference: LEDME LM5269

Rectangular LED panel 120x60 cm Bure Series with 80 W power and SMD 4014 font. It offers 6500 lm luminance, 81 lm/W efficiency and 4500 K color temperature.

View product online

Description

M LEDME’s Rectangular LED Series Bure Panel is an efficient lighting solution designed to deliver superior optical performance with No Flicker technology and UGR <19 dazzling control.

Technical characteristics

- Mark: M LEDME
- Watts: 80 w
- Light Source: Smd 4014
- Luminosity: 6500 lm
- Efficiency Lm: 81
- Working temperature: -20°C ~ +45°C
- Angle: 120°
- Useful Life: 30000 hours
- Protection: IP40
- Ik: 5
- Class Electrical insulation: II
- Overvoltage protection: 4 Kv
- Power supply: 170-265v ac
- Dimension: 1195X595X30H mm
- Material: Aluminium
- Driver: Philips
- Cri: 80

- UGR: <19
- Power Factor: 0.9
- Flicker Free: Yes
- Guarantee: 5 years
- Color temperature: 4500K ?? 6000K

Thanks to its high rate of chromatic reproduction and absence of blinking, this panel guarantees a visually comfortable and stable lighting in interior environments.

Specifications

Appliance class	Class II
Opening angle	120°
Cri (Ra)	80
Driver included	Yes
Manufacturer	Ledme
Lumens (lm)	6500 lm
Material	Aluminio
Power (W)	80 W
Protection	IP40
Nominal voltage (V)	170-265 V
Type of lamp	SMD 4014
Colour temperature	4500K
Estimated life (h)	30000
Usage	Indoor

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 23 November 2026