

Product sheet

Adjustable LED Track Downlight 15W Epistar 4500K

Brand: LEDME

Reference: LEDME LM4130



15W adjustable downlight with Epistar fountain and 1500 lumen luminance. Aluminium construction with 24° beam angle and 30000 hours service life. It operates between -20°C and 45°C, offering light efficiency of 100 lm/W.

[View product online](#)

Description

The M LEDME Focus Downlight Led Orientable Track is a 15W lighting device designed for rail systems, offering a versatile solution with Epistar light source and adjustable color temperature between 3000K, 4000K and 6000K.

Technical characteristics

- Watts: 15 w
- Light Source: Epistar
- Luminosity: 1500 lm
- Efficiency Lm: 100
- Working temperature: -20°C ~ +45°C
- Angle: 24°
- Useful Life: 30000 hours
- Protection: IP20
- Ik: 5
- Class Electrical insulation: II
- Power supply: 85-265v ac
- Dimension: 113X113X90H mm
- Cut dimension: 98 mm
- Material: Aluminium
- Cri: 80
- Ugr: <19

- Power Factor: 0.5
- Guarantee: 3 years

Its construction in aluminium and low Ugr index ensures efficient optical performance, while its wide working temperature range allows installation in various controlled environments.

Specifications

Appliance class	Class II
High	90 mm
Width	113 mm
Opening angle	24
Cri (Ra)	80
Diameter embedment (mm)	98 mm
EAN	8435579741306
Manufacturer	Ledme
Lumens (lm)	1500 lm
Material	Aluminio
Power (W)	15 W
Depth	113 mm
Protection	IP20
Nominal voltage (V)	85-265 V
Colour temperature	3000K
Estimated life (h)	30000

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, [contact our support team](#)

Item downloaded on 29 September 2026