Product sheet



LED Ceiling Light with Motion Sensor 15W 6000K

Brand: LEDME

Reference: LEDME LM8219

15W surface LED phone with Halls motion sensor and Epistar source. It offers 1200 lumens at 6000K, 80 lm/W efficiency and 30,000 hours of service life. 360° detection up to 6 meters with adjustable timer between 10 seconds and 2 minutes, regulated by day/night mode.

View product online

Description

The LED plafon with M LEDME motion sensor is an intelligent lighting solution designed to optimize energy consumption in indoor spaces, automatically activating the light according to the detected presence.

Technical characteristics

- Mark: M LEDME
- Power: 15 W
- Light source: Epistar
- Luminosity: 1200 lumens
- Light efficiency: 80 lm/W
- Beam angle: 120°
- Lifetime: 30,000 hours
- Protection: IP20
- Power supply: 170-265V AC
- Installation: Area
- Dimensions: 240x70H mm
- Materials: Aluminium and PC
- chromatic reproduction index (CRI): 80
- Guarantee: 3 years
- Color temperature: 4000K or 6000K
- Detection angle: 360°

- Detection distance: 6 meters
- Time range: 10 seconds to 2 minutes
- Regulation: Day/Night Mode

Thanks to its sensor with a 360° coverage angle and a distance of up to 6 meters, this device offers precise control in large areas. The regulation between day and night mode allows the sensitivity to be adjusted according to the needs of the environment.

Specifications

Cri (Ra)	80
Diameter	240 mm
Manufacturer	Ledme
Lumens (lm)	1200 lm
Material	Aluminio
Protection	IP20
Nominal voltage (V)	170-265V
Type of installation	Surface
Colour temperature	6000K
Usage	Indoor

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 9 November 2026