

Product sheet

Molded case circuit breaker 4P 100A 25kA

Brand: LEGRAND

Reference: LEGRAND 420215



4-pole molded case circuit breaker with a rated current of 100 A. Offers a breaking capacity of 25 kA at 400 V~ and adjustable overload protection between 80 and 100 A. Includes an integrated undervoltage release and threaded connection for fixed or DIN rail mounting.

[View product online](#)

Description

DPX³ 250 4-pole molded case circuit breaker, designed to protect electrical circuits against overloads and short circuits. This device provides an integrated and fixed protection solution, ensuring the safety and stability of electrical installations in industrial or commercial environments.

Technical features

- Rated current (In): 100 A
- Breaking capacity (Icu): 25 kA at 400 V~
- Rated voltage range: 220...690 V
- Thermal protection setting: 80...100 A
- Magnetic protection setting: 500...1000 A
- Number of poles: 4
- Main connection: Threaded
- Mounting: Compatible with DIN rail and top guide
- Auxiliary contacts: 1 NC, 1 changeover
- Protection rating: IP30
- Control element: Handle
- Undervoltage release: Integrated

This breaker allows precise adjustment of protection thresholds, adapting to the specific needs of the connected load. The presence of auxiliary contacts and a disconnection indicator facilitates integration into control and monitoring systems. Its compact design and the option for motorized operation make it

versatile for different mounting configurations.

Specifications

Rated current (A)	100
EAN	3245064202152
Manufacturer	LEGRAND
Range	Industrial
No. of poles	4P
Protection	IP30
Nominal voltage (V)	400 V

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 26 October 2026