

Product sheet

MCB 1P+N 25A C-curve 10kA

Brand: LEGRAND

Reference: LEGRAND 407758



1P+N miniature circuit breaker with a rated current of 25 A and C tripping curve. Protects installations against overloads and short circuits, achieving a breaking capacity of 10 kA according to EN 60947-2. Designed for flush mounting with a depth of 44 mm and a nominal voltage of 230 V AC.

[View product online](#)**Description**

1P+N miniature circuit breaker, designed to protect electrical installations against overloads and short circuits. It also allows for the control and isolation of the line.

Technical features

- Rated current: 25 A
- Nominal voltage: 230 V AC
- Tripping curve: C
- Breaking capacity: 6 kA (EN 60898) and 10 kA (EN 60947-2)
- Poles: 1+N (2 modules wide)
- Construction depth: 44 mm
- Protection rating: IP20
- Operating temperature: -25...70 °C
- Conductor connection: 1.5...25 mm² (flexible) and 1.5...35 mm² (rigid)
- Frequency: 50...60 Hz
- Current limiting class: 3
- Flush mounting: yes
- Simultaneous neutral switching: yes

This device offers a fast response to electrical faults thanks to its C curve and high breaking capacity. Its compact 2-module design facilitates integration into standard electrical panels, allowing the connection of conductors with a wide cross-section.

Specifications

Rated current (A)	25
Curve	C
EAN	3245064077583
Manufacturer	LEGRAND
# Elements	2
No. of poles	1P+N
Depth	44 mm
Protection	IP20
Rated voltage	230
Nominal voltage (V)	230

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 24 October 2026