

Product sheet

MCCB 2P 16A Curve D 10kA

Brand: LEGRAND

Reference: LEGRAND 408031



2-pole miniature circuit breaker with a rated current of 16 A and D tripping curve. Protects installations against overloads and short circuits, with a breaking capacity of 10 kA at 400 V according to EN 60947-2.

[View product online](#)**Description**

2-pole miniature circuit breaker designed to protect electrical installations against overloads and short circuits, while also allowing control and isolation of the network.

Technical features

- Rated current: 16 A
- Tripping curve: D
- Rated voltage: 400 V AC
- Breaking capacity: 6 kA at 400 V (EN 60898) and 10 kA at 400 V (EN 60947-2)
- Insulation voltage: 500 V
- Frequency: 50...60 Hz
- Protection rating: IP20
- Operating temperature: -25...70 °C
- Connection: 1.5...25 mm² (multiconductor) and 1.5...35 mm² (rigid)
- Dimensions: 2 modules wide, 44 mm deep

This device offers robust breaking capacity and a wide temperature range, ensuring operational stability in diverse environmental conditions. Its compact 2-module design facilitates integration into standard electrical panels.

Specifications

Rated current (A)	16
Width	44 mm
Curve	D
EAN	3245064080316
Manufacturer	LEGRAND
No. of poles	2P
Weight (kg)	0.4 kg
Protection	IP20
Cable cross-section (mm²)	35 mm²
Rated voltage	400

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 25 October 2026