

Product sheet

MCCB 2P 20A C Curve 10kA

Brand: LEGRAND

Reference: LEGRAND 407801



2-pole miniature circuit breaker with a rated current of 20 A and C tripping curve. Protects installations against overloads and short circuits, with a breaking capacity of 6 kA at 400 V according to EN 60898.

[View product online](#)**Description**

2-pole miniature circuit breaker designed to protect electrical installations against overloads and short circuits. It also allows for the control and isolation of the installation, offering a reliable solution for current management in low-voltage circuits.

Technical features

- Rated current: 20 A
- Tripping curve: C
- Nominal voltage: 400 V AC
- Breaking capacity: 10 kA at 400V (EN 60947-2) and 6 kA at 400V (EN 60898)
- Nominal insulation voltage (Ui): 500 V
- Maximum impulse voltage (Uimp): 4 kV
- Frequency: 50...60 Hz
- Current limiting class: 3
- Protection rating: IP20
- Operating temperature: -25...70 °C
- Connection cross-section: 1.5...25 mm² (multiple conductors) and 1.5...35 mm² (rigid cable)
- Dimensions: 2 modules wide, 44 mm deep
- Flush mounting: yes

This device guarantees a fast response to electrical faults, protecting connected equipment and the integrity of the installation. Its compact 2-module design facilitates integration into standard electrical

panels, while its versatile connection capacity adapts to different types of wiring.

Specifications

Rated current (A)	20
Curve	C
EAN	3245064078016
Manufacturer	LEGRAND
Measures	2 módulos de anchura, 44 mm de profundidad
No. of poles	2P
Protection	IP20
Rated voltage	400
Nominal voltage (V)	400 V

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, [contact our support team](#)

Item downloaded on 24 October 2026