Product sheet



Molded case circuit breaker 3P 25A C curve

Brand: LEGRAND

Reference: LEGRAND 407861

3-pole circuit breaker with a rated current of 25 A and C tripping curve. Designed to protect installations against overloads and short circuits, with a breaking capacity of 10 kA at 230V according to EN 60898. Its construction depth is 44 mm, occupying 3 modules, and it accepts rigid cables from 1.5 to 35 mm².

View product online

Description

3-pole circuit breaker designed to protect electrical installations against overloads and short circuits. It also allows for the control and isolation of the installation. Its compact 3-module design and 44 mm depth facilitate integration into electrical panels, supporting a rated current of 25 A and a nominal voltage of 400 V AC.

Technical features

- Tripping curve: C
- Rated current: 25 A
- Rated voltage: 400 V AC
- Rated insulation voltage (Ui): 500 V
- Rated impulse voltage (Uimp): 4 kV
- Breaking capacity (EN 60898): 10 kA at 230 V and 6 kA at 400 V
- Breaking capacity (EN 60947-2): 25 kA at 230 V and 10 kA at 400 V
- Frequency: 50...60 Hz
- Current limiting class: 3
- Protection rating: IP20
- Operating temperature: -25...70 °C
- Connection cross-section: 1.5...25 mm² (multiple conductors) and 1.5...35 mm² (rigid cable)
- Flush mounting: Yes

This device offers a reliable response to electrical faults thanks to its C tripping curve and its breaking capacity certified under EN standards. Compatibility with additional equipment and its wide temperature range guarantee versatility in different operating conditions.

Specifications

Rated current (A)	25
Curve	C
EAN	3245064078610
# Elements	3
No. of poles	3P
Protection	IP20
Rated voltage	400

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 3 November 2026