

Product sheet

Magnetic circuit breaker 2P 6A C curve 10kA

Brand: LEGRAND

Reference: LEGRAND 403604



2-pole magnetothermic switch with 6 A assigned current and C firing curve. Protects installations against overloads and short circuits, with cutting power from 10 kA to 230 V and 6 kA to 400 V. It occupies 2 DIN modules, depth of 44 mm, rated voltage 230/400 V~ and insulation of 500 V. It meets EN 60898 and EN 60947-2 standards, suitable for flush mounting on standard electrical enclosures.

[View product online](#)

Description

2-pole magnetothermic switch designed for the protection of electrical installations against overloads and short circuits. It also allows the control and isolation of the installation. Its compact design occupies 2 modules and is designed for flush mounting, facilitating its integration into standard electrical frames.

Technical characteristics

- Assigned current: 6 A
- Nominal voltage: 230/400 V~
- Shot curve: C
- Number of poles: 2 (protected)
- Cutting power: 10 kA to 230V and 6 kA to 400V (according to EN 60898 and EN 60947-2)
- Insulation voltage (Ui): 500 V
- Maximum pulse rate (Uimp): 4 kV
- Frequency: 50...60 Hz
- Intensity limitation class: 3
- Degree of protection: IP20
- Construction depth: 44 mm
- Width: 2 modules

This device offers a reliable response to electrical failures, ensuring the safety of the installation and connected equipment. The compatibility with additional equipment allows the protection to be adapted to specific needs without complicating the assembly.

Specifications

Rated current (A)	6
Curve	C
EAN	3245064036047
Manufacturer	LEGRAND
Long	2 módulos
No. of poles	2P
Depth	44 mm
Protection	IP20

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 30 October 2026