

Product sheet

Circuit Breaker 3P 32A 400V Curve C 3 Modules

Brand: LEGRAND

Reference: LEGRAND 403619



3-pole magnetothermal switch with 32 A assigned current and C firing curve. Designed for protection against overloads and short circuits in 400 V AC installations. It offers a cutting power from 6 kA to 400 V and occupies 3 modules in the frame.

[View product online](#)

Description

3 pole magnetothermal switch designed for the protection of electrical installations against overloads and short circuits. It also allows the control and isolation of the installation. Its compact design occupies 3 modules and is designed for flush mounting.

Technical characteristics

- Assigned current: 32 A
- Nominal voltage: 400 V AC
- Shot curve: C
- Number of poles: 3 (all protected)
- Cutting power: 10 kA to 230 V and 6 kA to 400 V (according to EN 60898 and EN 60947-2)
- Nominal insulation voltage (Ui): 500 V
- Maximum pulse rate (Uimp): 4 kV
- Frequency: 50...60 Hz
- Intensity limitation class: 3
- Degree of protection: IP20
- Construction depth: 44 mm
- Installation to a minimum: Yes

This device provides a reliable response to electrical failures, ensuring network security and connected equipment. Compatibility with additional equipment allows the protection to be adapted to specific installation needs.

Specifications

Rated current (A)	32
Curve	C
EAN	3245064036191
Manufacturer	LEGRAND
No. of poles	3P
Depth	44 mm
Protection	IP20
Rated voltage	400

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 30 October 2026