

Product sheet

Automatic molded case 4P 630 A 36 kA

Brand: LEGRAND

Reference: LEGRAND 422009



4-pole DPX³ molded case circuit breaker with a rated current of 630 A and a breaking capacity of 36 kA at 400 V. Includes adjustable thermal protection between 504 and 630 A, magnetic protection from 3150 to 6300 A, and an integrated undervoltage release.

[View product online](#)

Description

4-pole magnetothermal molded case circuit breaker with a rated current of 630 A, designed to protect electrical circuits against overloads and short circuits. This device offers a robust and reliable solution for industrial and commercial installations that require a high degree of safety and control in energy management.

Technical features

- Rated permanent current (Iu): 630 A
- Rated voltage range: 220...690 V
- Breaking capacity (Icu) at 400 V, 50 Hz: 36 kA
- Overload protection range adjustment: 504...630 A
- Short-circuit release with delay: 3150...6300 A
- Short-circuit release without delay: 3150...6300 A
- Number of poles: 4
- Main circuit connection: Threaded
- Control element: Handle
- Protection rating: IP30
- 2 normally closed auxiliary contacts and 2 changeover contacts
- Includes undervoltage release and disconnection indicator

The integrated fixed construction ensures a safe and stable installation. The availability of an optional motorized actuator allows for the automation of operations, improving operational efficiency in

advanced control systems.

Specifications

Rated current (A)	630
EAN	3414970378057
Manufacturer	LEGRAND
Range	Industrial
# Elements	4
No. of poles	4P
Protection	IP30
Nominal voltage (V)	400 V

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, [contact our support team](#)

Item downloaded on 25 October 2026