

Product sheet

Livinglight Card Switch 2 Modules Black

Brand: LEGRAND

Reference: LEGRAND LN4549



2-module Livinglight card switch for recessed mounting, designed to control power supply in hotel rooms by inserting a card. It works at 230 V with an assigned current of 2 A and connection by screwed terminals.

[View product online](#)

Description

2 Module Livinglight Card Switch designed to control power supply in hotel rooms by inserting a card. This device allows you to manage the circuit safely and efficiently, activating the power only when the corresponding card is introduced.

Technical characteristics

- Material: Thermoplastic halogen-free plastic
- Colour: Black (RAL 7021) with matt finish
- Nominal voltage: 230 V
- Allocation current: 2 A
- Switching intensity for fluorescent lamps: 2 AX
- Degree of protection: IP20
- Connection: Screwed-up terminal
- Dimensions: 22 mm wide, 44 mm high and 40 mm deep
- Construction depth: 29 mm
- Minimum installation box depth: 39 mm
- Method of assembly: Embedded in cast

This switch offers a practical solution for energy control in hotel environments, ensuring reliable operation and aesthetic integration thanks to its modular design and matt finish.

Specifications

Rated current (A)	2
Colour	Black
EAN	8005543441725
Manufacturer	LEGRAND
Long	44 mm
Halogen-free	Yes
Material	Termoplástico
Measures	22 mm x 44 mm x 40 mm
Weight (kg)	0.1
Depth	40 mm
Protection	IP20
Rated voltage	230
Nominal voltage (V)	230 V

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 26 October 2026