Product sheet

MCCB 1P+N 10A C-curve 230V 2 modules

Brand: LEGRAND

Reference: LEGRAND 449925

1P+N miniature circuit breaker (MCB) rated at 10 A with C-curve for 230 V. Protects against overloads and short circuits with a breaking capacity of 6 kA. Occupies 2 modules, accepts conductors from 1.5 to 25 mm², and simultaneously switches the neutral. Complies with EN 60898, with 500 V insulation and a 4 kV impulse rating. Flush mounting, IP20, operating temperature from -25 to 70 °C.

View product online

Description

1-pole plus neutral miniature circuit breaker (MCB), designed to protect electrical installations against overloads and short circuits. It also allows for manual control and isolation of the line.

Technical features

- Rated current: 10 A
- Nominal voltage: 230 V AC
- Trip curve: C
- Breaking capacity: 6 kA (per EN 60898)
- Width: 2 modules
- Depth: 44 mm
- Protection rating: IP20
- Operating temperature: -25...70 °C
- Conductor connection: 1.5...25 mm² (stranded) / 1.5...35 mm² (solid)
- Simultaneous neutral switching: yes
- Current limiting class: 3
- Overvoltage category: 3

This device offers a fast response to electrical faults thanks to its C-curve and high breaking capacity. Its

compact 2-module design facilitates integration into standard electrical panels, while simultaneous neutral switching ensures safe isolation of the installation.

Specifications

Rated current (A)	10
Curve	C
EAN	3414972963411
Manufacturer	LEGRAND
# Elements	1
No. of poles	1P+N
Protection	IP20
Rated voltage	230

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 30 October 2026