

Product sheet

Miniature Circuit Breaker 1P+N 16A C Curve 230V 1 Module

Brand: LEGRAND

Reference: LEGRAND 434991



1-pole plus neutral miniature circuit breaker with a rated current of 16 A and C tripping curve. Designed to protect electrical installations against overloads and short circuits, offering a breaking capacity of 6 kA in accordance with EN 60898.

[View product online](#)

Description

1-module miniature circuit breaker designed to protect electrical installations against overloads and short circuits. This device also allows for the control and isolation of the installation, ensuring operational safety in single-phase circuits.

Technical features

- Rated current: 16 A
- Rated voltage: 230 V AC
- Tripping curve: C
- Number of poles: 1P+N (1 protected pole)
- Breaking capacity: 6 kA according to EN 60898
- Construction depth: 44 mm
- Width: 1 module
- Protection rating: IP20
- Operating temperature: -25...70 °C
- Conductor connection: 0.75...10 mm² (flexible) and 0.75...16 mm² (rigid)
- Simultaneous neutral switching: Yes

Simultaneous neutral switching and the C tripping curve provide a precise response to electrical faults. Its compact 1-module design facilitates integration into standard electrical panels, while the IP20 protection rating makes it suitable for use in dry indoor environments.

Specifications

Rated current (A)	16
Curve	C
EAN	3414973045130
Manufacturer	LEGRAND
No. of poles	1P+N
Depth	44 mm
Protection	IP20
Rated voltage	230

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 30 October 2026