

Product sheet

MCB 1P+N 25A C-curve 230V 1 module

Brand: LEGRAND

Reference: LEGRAND 434993



1-module miniature circuit breaker (MCB) with 25 A and C-curve for protection against overloads and short circuits. Designed for 230 V AC installations, it offers a breaking capacity of 6 kA according to EN 60898.

[View product online](#)**Description**

1-module miniature circuit breaker (MCB) designed to protect electrical installations against overloads and short circuits. It also allows for the control and isolation of the line, offering a compact and functional solution for electrical panels.

Technical features

- Rated current: 25 A
- Nominal voltage: 230 V AC
- Trip curve: C
- Number of poles: 1P+N (2 total poles, 1 protected)
- Breaking capacity: 6 kA according to EN 60898
- Maximum impulse voltage (Uimp): 4 kV
- Width: 1 module
- Construction depth: 44 mm
- Protection rating: IP20
- Operating temperature: -25...70 °C
- Conductor connection: 0.75...10 mm² (multi-strand) and 0.75...16 mm² (solid)
- Simultaneous switching of neutral: Yes
- Current limitation class: 3

This device guarantees a precise response to electrical faults thanks to its C trip curve and high breaking capacity. Its 1-module design facilitates integration into standard panels, while the

simultaneous switching of the neutral ensures complete isolation of the installation.

Specifications

Rated current (A)	25
Curve	C
EAN	3414973045192
Manufacturer	LEGRAND
No. of poles	1P+N
Depth	44 mm
Protection	IP20
Rated voltage	230
Nominal voltage (V)	230

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, [contact our support team](#)

Item downloaded on 26 October 2026