Product sheet

MCCB RX 1P+N 25A C-curve 230V 2 modules

Brand: LEGRAND

Reference: LEGRAND 449928

25 A and 230 V miniature circuit breaker with C tripping curve. Protects installations against overloads and short circuits, with a breaking capacity of 6 kA according to EN 60898. Occupies 2 modules and allows simultaneous switching of the neutral.

View product online

Description

1P+N miniature circuit breaker designed to protect electrical installations against overloads and short circuits. This device also allows controlling and isolating the installation when necessary, offering a reliable solution for cutting off current in single-phase circuits.

Technical features

- Rated current: 25 A
- Rated voltage: 230 V AC
- Tripping curve: C
- Breaking capacity: 6 kA according to EN 60898
- Width: 2 modules
- Construction depth: 44 mm
- Protection rating: IP20
- Operating temperature: -25...70 °C
- Conductor connection: 1.5...25 mm² (flexible) and 1.5...35 mm² (rigid)
- Simultaneous neutral switching: yes
- Current limitation class: 3
- Overvoltage category: 3

Simultaneous neutral switching ensures effective isolation of the circuit. Its compact 2-module design facilitates integration into standard electrical panels. The wide connection capacity allows the use of different types of cabling, optimizing installation in environments with pollution degree 2.

Specifications

Rated current (A)	25
Curve	C
EAN	3414972963503
Manufacturer	LEGRAND
No. of poles	1P+N
Depth	44 mm
Protection	IP20
Rated voltage	230

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 30 October 2026