

Product sheet

MCB 1P+N 40A C Curve 230V 1 Module

Brand: LEGRAND

Reference: LEGRAND 434995



1-module miniature circuit breaker with 1 protected pole and neutral, 40 A and 230 V AC. C tripping curve and 6 kA breaking capacity according to EN 60898. Depth of 44 mm, IP20 and connection for conductors from 0.75 to 10 mm². Designed for protection against overloads and short circuits in electrical installations.

[View product online](#)

Description

1-pole plus neutral miniature circuit breaker designed to protect electrical installations against overloads and short circuits. It also allows for the control and isolation of the line. Its compact 1-module design facilitates integration into standard electrical panels.

Technical features

- Rated current: 40 A
- Nominal voltage: 230 V AC
- Tripping curve: C
- Breaking capacity: 6 kA according to EN 60898
- Poles: 1 protected + 1 neutral
- Construction depth: 44 mm
- Protection rating: IP20
- Operating temperature: -25...70 °C
- Connection cross-section: 0.75...16 mm² (rigid cable)

Simultaneous switching of the neutral ensures safe disconnection of all conductors. The current limiting class 3 helps reduce thermal effects during faults. Compatible with additional equipment according to manufacturer specifications.

Specifications

Rated current (A)	40
Curve	C
EAN	3414973045253
Manufacturer	LEGRAND
No. of poles	1P+N
Depth	44 mm
Protection	IP20
Cable cross-section (mm²)	10 mm²
Rated voltage	230

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, [contact our support team](#)

Item downloaded on 28 October 2026